| 型 PRODUCT | 號 NO. | PA-40P.0 | (4" HORN) |
|--------------|----------|----------|-----------|
| 備 REMARI | 註 | | |



| ادر الله الله الله الله الله الله الله الل | | the the | Netst A. D. Adve Let | | | |
|--|-----------------------------|------------------------------|----------------------------|--|--|--|
| 編號 項 目 | | 規格 | 測 試 條 件 | | | |
| ITEM DESCRIPTION | | SPECIFICATION | TEST CONDITION | | | |
| 1 | 音 圈 阻 抗 VOICE COIL IMP. | 4 Ohm +/- 15 %Ohm | AT 1k Hz | | | |
| 2 | 音 圏 規 格 VOICE COIL SIZE | (Dia.) 25.4 mm | | | | |
| 3 | 磁 鐵 規 格 MAGNET SIZE | 60 mmX 32 mmX 8 mm | WEIGHT 3 Oz | | | |
| 4 | 動作試驗 OPERATION | MUST BE NORMAL | PROGRAM SOURCE V | | | |
| 5 | 異常 BUZZES & RATTLES | MUST BE NORMAL | SIN WAVE V | | | |
| 6 | 最低共振頻率 RESONANT FREQ. fo | 700 Hz +/- 20 %Hz | WITHOUT BAFFLE | | | |
| 7 | 實效頻率範圍 FREQ. RESPONSE | fo ~ 7 K Hz | | | | |
| 8 | 額定頻率範圍 RATED FREQ. RESP. | 700 ~ 7 K Hz | | | | |
| 9 | 額 定 入 力 RATED POWER INPUT | 10 Watts | | | | |
| 10 | 最 大 入 力 MAX. POWER INPUT | 15 Watts | | | | |
| 11 | 連續 DOAD TEST | AFTER TESTED 4&5 | White Noise10Watts 4 Hours | | | |
| 12 | 淨 重 NET WEIGHT | 370 Grams +/- 5 Grams | | | | |
| 13 | 輸出音壓 OUTPUT S. P. L. | MEAN VALUEAT 100 +/- 3 dB | AT 1 M 1 Watt AXIS CAL. | | | |
| 14 | | | | | | |

| | | 4 | | | | | | | + | |
|--|--------------------------|--------|--------|-------------------|----------|----------|------|------|-------|--------|
| Rev. | Pev. Date Description | | | | | | Re | mark | | |
| YUBRIC | YUE | BRIGHT | CO., | LTD. | P/N | PA-40P.0 |) | | | |
| Title | ABS PLASTIC HORN SPEAKER | | | Dwg. No. PA40P001 | | | | | | |
| A DO LE ONC HORITOR EXCER | | | | Date | 20151118 | Rev. | Α | RoHS | ~ | |
| Unless otherwise specified, demensions are in millimeters. | | | File | SUT014 | Drw. | b37 | App. | b37 | | |
| | | | 11,-11 | | | | | Q2M- | 01-04 | Rev. A |