



SPECIFICATION

- (1) ITEM NO. : BH-511A-152MM
- (2) WIRE: UL1007 AWG #26
 BLACK & RED: 152MM±5MM
 STRIP & TIN: 5MM±1MM
- (3) HOLDER MATERIAL: PP RESIN, BLACK COLOR
- (4) SPRING MATERIAL: Ø0.5 MM SPRING STEEL NICKEL PLATED
- (5) RIVET MATERIAL: BRASS NICKEL PLATED
- (6) RoHS COMPLIANT

3			COMFORTABLE ELECTRONIC CO.LTD.																		
2																					
1																					
NO.	MODIFICATION	DATE	NAME	BATTERY HOLDER: BH-511A-152MM																	
			SCALE	2:1	APPD																
<table border="1"> <tr> <th colspan="4">General Tolerances</th> </tr> <tr> <td>0 ~ >3</td> <td>± 0.10</td> <td>30 ~ >120</td> <td>± 0.30</td> </tr> <tr> <td>3 ~ >6</td> <td>± 0.10</td> <td>120 ~ >400</td> <td>± 0.50</td> </tr> <tr> <td>6 ~ >30</td> <td>± 0.20</td> <td colspan="2">Angle: ± 3°</td> </tr> </table>			General Tolerances				0 ~ >3	± 0.10	30 ~ >120	± 0.30	3 ~ >6	± 0.10	120 ~ >400	± 0.50	6 ~ >30	± 0.20	Angle: ± 3°		The Third Angle Projection		
General Tolerances																					
0 ~ >3	± 0.10	30 ~ >120	± 0.30																		
3 ~ >6	± 0.10	120 ~ >400	± 0.50																		
6 ~ >30	± 0.20	Angle: ± 3°																			
			UNIT	MM	CHKD																
			MAT'L	SEE SPEC.	DWN																
			DATE	MAR. 11. 2013	DR NO	511A-0313															